

# COMPARATIVE CHART OF COMPLIANT SPECTROLINE® UV-A LED LAMPS

	PART #	HAND-HELD	OVERHEAD	LITHIUM-ION OPERATED (RECHARGEABLE)	NiMH BATTERY PACK OPTION (AC/DC)	CLEAR/BOROFLOAT® FILTER PROTECTOR	INTERNAL/INTEGRAL BLACK LIGHT FILTER	ADDITIONAL WHITE LIGHT LED	NOMINAL STEADY-STATE UV-A (365 nm) INTENSITY at 15 in (38 cm)	UV-A COVERAGE AREA at 15 in (38 cm) at minimum 1,200 µW/cm²
<b>ASTM E3022 &amp; RRES 90061 (Rolls-Royce) Compliant Lamps</b>										
	<b>TRITAN™ 365</b>	TRI-365SBLC	●			●	●	●	4,500 µW/cm²	5.5 in (14 cm)
	<b>PowerMAX™ 365</b>	PM-1600SBLC		●		●	●	●	4,500 µW/cm²	15 x 6 in (38 x 15 cm)
<b>ASTM E3022 Compliant Lamps</b>										
	<b>QUADRAN™ 365</b>	QDR-365SC	●			●	●	●	3,700 µW/cm²	6 in (15 cm)
	<b>TRITAN™ 365</b>	TRI-365HC	●			●	●	●	7,000 µW/cm²	6 in (15 cm)
<b>Wavelength Compliant Lamps</b>										
	<b>QUADRAN™ 365 S-Series</b>	QDR-365SA				●		●	4,500 µW/cm²	6.5 in (16.5 cm)
	<b>QUADRAN™ 365 AC/DC Mobile Versions</b>	QDR-365MSA	●		●	●		●	4,500 µW/cm²	6.5 in (16.5 cm)
		QDR-365MSBLA	●		●	●	●	●	4,500 µW/cm²	6.5 in (16.5 cm)
	<b>TRITAN™ 365 Series</b>	TRI-365HB	●			●		●	9,000 µW/cm²	6.5 in (16.5 cm)
		TRI-365DB	●			●		●	< 5,000 µW/cm²	5.5 in (14 cm)
	<b>TRITAN™ 365 AC/DC Mobile Versions</b>	TRI-365MHB	●		●	●		●	9,000 µW/cm²	6.5 in (16.5 cm)
TRI-365MDB		●		●	●		●	< 5,000 µW/cm²	5.5 in (14 cm)	
TRI-365MDBB		●		●	●	●	●	< 5,000 µW/cm²	4 in (10 cm)	
	<b>PowerMAX™ 365</b>	PM-1600UV		●		●			4,500 µW/cm²	15 x 6 in (38 x 15 cm)
	<b>OPTI-LUX™ 365 Series</b>	OLX-365	●		●				10,000 µW/cm²	2 in (5 cm)
		OLX-365B	●		●		●		10,000 µW/cm²	2 in (5 cm)
		OLX-365FL	●		●				4,500 µW/cm²	2.5 in (6.3 cm)
		OLX-365BFL	●		●			●	4,500 µW/cm²	2.5 in (6.3 cm)
	<b>EagleEye™</b>	EE-365	●		●			●	4,500 µW/cm²	5.5 in (14 cm)